



US008347583B2

(12) **United States Patent**
Cashman

(10) **Patent No.:** **US 8,347,583 B2**
(45) **Date of Patent:** ***Jan. 8, 2013**

(54) **BUILDING TRIM**

(76) Inventor: **Daniel J. Cashman**, Suffield, CT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/928,994**

(22) Filed: **Dec. 22, 2010**

(65) **Prior Publication Data**

US 2011/0094172 A1 Apr. 28, 2011

Related U.S. Application Data

(63) Continuation-in-part of application No. 12/152,112, filed on May 12, 2008, now Pat. No. 7,874,108, and a continuation of application No. 12/383,976, filed on Mar. 31, 2009.

(51) **Int. Cl.**

E04B 1/00 (2006.01)

E06B 1/00 (2006.01)

E06B 3/00 (2006.01)

(52) **U.S. Cl.** ... **52/718.01**; 52/213; 52/204.1; 52/204.54; 52/581; 52/717.01; 52/519

(58) **Field of Classification Search** 52/287.1, 52/204.54, 588.1, 204.1, 204.53, 94-96, 52/198, 288.1, 716.1, 718.04, 717.05, 717.06, 52/204, 55, 204.56, 745.16, 208-213, 204.5, 52/745.15, 716.8, 717.01, 718.01

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,197,913 A 4/1940 Axe
2,378,163 A 6/1945 Thomas

3,214,873 A	11/1965	Davis	
3,499,248 A	3/1970	Baer	
4,027,431 A	6/1977	Rackard	
4,196,553 A	4/1980	Veach	
4,222,200 A	9/1980	Beirnes	
4,275,526 A	6/1981	Abramson	
4,319,439 A	3/1982	Gussow	
4,327,528 A *	5/1982	Fritz	52/309.1
4,624,091 A	11/1986	Biro	
4,706,426 A	11/1987	Rumsey	
4,903,449 A	2/1990	Ellingson, Jr.	
5,560,170 A *	10/1996	Ganser et al.	52/539
5,664,376 A	9/1997	Wilson et al.	
5,768,839 A	6/1998	McCabe	
5,974,748 A	11/1999	Sciuga et al.	
6,341,458 B1	1/2002	Burt	
6,354,049 B1	3/2002	Bennett	
6,553,732 B2 *	4/2003	Shaw	52/287.1
6,631,600 B2	10/2003	Schiedegger et al.	

(Continued)

Primary Examiner — Jeanette E. Chapman

(74) *Attorney, Agent, or Firm* — Alix, Yale & Ristas, LLP

(57) **ABSTRACT**

A trim element such as a door pilaster or frieze board, for attachment to a building wall, having front and back longitudinal faces, first and second longitudinal edges, and a longitudinal groove in the first edge. A mounting bracket for the wall has a forward strip that extends laterally and is selectively friction fit into the groove, a back strip that extends laterally on the back face of the element, and a connecting web between the forward and back strip that is flush with the first edge when the forward strip is fully inserted in the groove. A mounting flange for the wall extends laterally from the back face of the element, beyond the second longitudinal edge, and has a longitudinal channel along the second edge with a width that is effective to receive an edge of wall siding.

9 Claims, 8 Drawing Sheets

