

(12) **United States Patent**
Cashman

(10) **Patent No.:** **US 8,601,768 B2**
(45) **Date of Patent:** **Dec. 10, 2013**

(54) **BUILDING TRIM**

52/717.05, 717.06, 210, 717.01, 204.54,
52/588.1, 204.1, 204.53, 94-96, 198,
52/288.1, 204.55, 204.56, 745.16,
52/208-213, 204.5, 745.15

(71) Applicant: **Daniel J. Cashman**, Suffield, CT (US)

(72) Inventor: **Daniel J. Cashman**, Suffield, CT (US)

See application file for complete search history.

(73) Assignee: **Trim Solutions, LLC**, East Windsor, CT (US)

(56) **References Cited**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

U.S. PATENT DOCUMENTS

(21) Appl. No.: **13/735,452**

3,038,571 A *	6/1962	Clements	52/464
4,608,800 A *	9/1986	Fredette	52/656.1
5,711,117 A *	1/1998	Zaccagni et al.	52/94
7,669,382 B2 *	3/2010	Burton et al.	52/745.16
8,006,445 B2 *	8/2011	Burton et al.	52/204.55

(22) Filed: **Jan. 7, 2013**

* cited by examiner

(65) **Prior Publication Data**

US 2013/0118111 A1 May 16, 2013

Primary Examiner — Jeanette E. Chapman

(74) *Attorney, Agent, or Firm* — Alix, Yale & Ristas, LLP

Related U.S. Application Data

(60) Division of application No. 12/928,994, filed on Dec. 22, 2010, now Pat. No. 8,347,583, which is a continuation-in-part of application No. 12/152,112, filed on May 12, 2008, now Pat. No. 7,874,108, and a continuation of application No. 12/383,976, filed on Mar. 31, 2009, now Pat. No. 8,141,308.

(57) **ABSTRACT**

A trim element such as a door pilaster or frieze board, for attachment to a building wall, having front and back longitudinal faces, first and second longitudinal edges, and a longitudinal groove in the first edge. A mounting bracket for the wall has a forward strip that extends laterally and is selectively friction fit into the groove, a back strip that extends laterally on the back face of the element, and a connecting web between the forward and back strip that is flush with the first edge when the forward strip is fully inserted in the groove. A mounting flange for the wall extends laterally from the back face of the element, beyond the second longitudinal edge, and has a longitudinal channel along the second edge with a width that is effective to receive an edge of wall siding.

(51) **Int. Cl.**
E04B 1/00 (2006.01)
E06B 1/00 (2006.01)
E06B 3/00 (2006.01)

(52) **U.S. Cl.**
USPC **52/718.01**; 52/213; 52/204.1; 52/204.54;
52/581; 52/717.01; 52/519

(58) **Field of Classification Search**
USPC 52/716.8, 718.01, 718.04, 287.1, 716.1,

11 Claims, 8 Drawing Sheets

